Satisfy Professional's Needs

Cordless Driver Drill
DF347D 10mm (3/8") / DF457D 13mm (1/2")

Cordless Hammer Driver Drill
HP347D 10mm (3/8") / HP457D 13mm (1/2")

LIGHTER

1.1Ah Lithium-ion Series

All metal gear construction for extra high transmission durability

Gear case
covers gears completely
for increased durability against dust.

Torque setting :
16 stage + drill mode

Mechanical 2-speed gearing
- High speed mode for speedy drilling in light duty applications
- Low speed mode for heavy duty applications requiring high torque

Single sleeve keyless chuck
allows for easy bit installation/removal with one hand.

Push button type reverse switch

Variable speed control by trigger

Rubberized soft grip
provides more control and reduced fatigue.

HP457D

14.4V Li-ion

Battery For Model:
DF347D, HP347D

BL1411G **1.1Ah**

18V Li-ion

Battery For Model:
DF457D, HP457D

BL1811G **1.1Ah**

Charger : DC18WA

Charging Time 60 min.

DF347D

DF457D

HP347D

Cordless Driver Drill / Cordless Hammer Driver Drill — DF347D / DF457D / HP347D / HP457D

- Variable Speed
- Electric Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 16
- Carrying Case

	Driver Drill DF347D 14.4V Li-ion	Driver Drill DF457D 18V Li-ion	Hammer Driver Drill HP347D 14.4V Li-ion	Hammer Driver Drill HP457D 18V Li-ion
Capacity	Steel : 10mm (3/8")	Steel : 13mm (1/2")	Steel : 10mm (3/8")	Steel : 13mm (1/2")
	Wood : 25mm (1")	Wood : 36mm (1-7/16")	Wood : 25mm (1")	Wood : 36mm (1-7/16")
	-	-	Masonry : 10mm (3/8")	Masonry : 13mm (1/2")
Impacts per minute (ipm)	-	-	Hi : 0-21,000	Hi : 0-21,000
	-	-	Lo : 0-6,000	Lo : 0-6,000
No load speed (rpm)	Hi : 0-1,400	Hi : 0-1,400	Hi : 0-1,400	Hi : 0-1,400
	Lo : 0-400	Lo : 0-400	Lo : 0-400	Lo : 0-400
Max. fastening torque	Hard / Soft : 30 / 15N.m	Hard / Soft : 42 / 24N.m	Hard / Soft : 30 / 15N.m	Hard / Soft : 42 / 24N.m
Dimensions (L x W x H)	198x83x235mm (7-3/4"x3-1/4"x9-1/4")	221x83x240mm (8-3/4"x3-1/4"x9-1/2")	216x83x235mm (8-1/2"x3-1/4"x9-1/4")	239x83x240mm (9-3/8"x3-1/4"x9-1/2")
Net weight*	1.4kg (3.2lbs)	1.7kg (3.7lbs)	1.5kg(3.3lbs)	1.7kg (3.8lbs)

Standard Equipment : Charger, Battery Cartridge, (+) (-) Bit

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BB-AD